NOTICE TO CONTRACTOR

CALL BEFORE YOU DIG
NORTH DAKOTA
UTILITIES UNDERGROUND LOCATION SERVICE
1-800-795-0555

Copyright © 2018 by Swenson, Hogen & Co. All rights reserved. No part of this drawing may be used or in any form or by any means without the express written per Swenson Hogen & Co.

PAVEMENT

- PI) ON SITE EXTERIOR CONCRETE MATERIALS AND CONSTRUCTION MATERIALS SHALL CONFORM TO CITY OF BUSIARCX SPECIFICATIONS EXCEPT AS MODIFIED HERBIN. AUR CONTENT SHALL BE 5% TO 7%. STRENGTH AT 28 DAYS SHALL BE 4500 PG.
- P2) 5" CONCRETE WITH FIBERMESH AND 6" CLASS V BASE.
- (P3) ISOLATION JOINTS WILL BE REQUIRED ALONG THE BUILDING, STOOPS AND ALL FIXED ITEMS, LEAVE JOINT W. LOW AND SEAL, ISOLATION JOINTS SHALL BE SEALED USING A ONE PART POLYURETHANE THE SEALANT.
- (P4) CONSTRUCTION JOINTS MILL BE PLACED TO COINCIDE WITH CONTRACTION JOINT SPACING, CONSTRUCTION JOINT FOR UNREMPORCED CONCRETE SHALL HAVE A MINIMUM 13" DAMETER HALF ROUND KEYMAY OR APPROVED EQUAL, CONSTRUCTION JOINTS FOR REINFORCED CONCRETE SHALL BE 1/2" X 12" DOWELS AT 12 O/C.
- (P5) SUBGRADE PREPARATION UNDER AREAS TO BE PAVED SHALL BE 6" THICK AND SHALL COUPLY WITH CITY OF BISMARCK SPECIFICATIONS EXCEPT DENSITY SHALL BE 95% OF ASTM D 698.

SIGNAGE & PAVEMENT STRIPING

- ISTI ALL NON-ADA STRIPING SHALL BE 4" MIDE NON REFLECTORIZED PAINT MEETING THE REQUIREMENTS OF AASHTO M28 APPLIED AT A RATE OF 110 SQUARE FEET PER GALLON. COLOR SHALL BE YELLOW. TYPICAL FOR ALL STRIPING UNLES OTHERWISE NO
- SSI ADA STRIPING FOR LANES AND SYMBOLS SHALL BE BLUE PAINT MEETING THE REQUIREMENT OF AASHTO W28 APPLIED AT A RATE OF 110 SOURSE FEET PER CALLON. PAINT FACE AND TOP OF CURB (6" MOE) IN FRONT OF ALL HANDICAP STALLS.
- PROVIDE AND INSTALL ADA SIGNS.

(1) INSTALL 6' OPAQUE VINYL FENCE FOR TRASH ENCLOSURE

GENERAL LANDSCAPING NOTES FOR ALL SHEETS

SHALL BE PLACED ON A FOOTING & FOUNDATION
-GRADE SHALL BE 11 ABOVE PAYEMENT
BOLLARD SHALL BE CENTERED ONE FOOT FROM END OF WALL
-WALL SHALL BE CONTEND ONE FOOT IN MOTH
-PLACE JA FEBRA 2 FEET ON CENTER EACH WAY.


BOLLARD NOT TO SCALE

- ALL CONTRACTORS WISHING TO SUBMIT BIDS FOR THIS LANDSCAPING PROJECT SHALL BE RESPONSIBLE FOR FIELD VERIFYING ALL CONDITIONS.
- PROTECT THE IMPROVEMENTS ON SITE AND ON THE ADJOINING PROPERTIES. PROVIDE BARRICADES, COVERINGS OR OTHER TYPE OF PROTECTION AS NECESSARY TO PREVENT DAMAGE AND TO SAFEGUARD AGAINST INJURY TO EMISTING UTILITIES.
- ALL PLANTING BEDS SHALL BE INSTALLED WITH 3" OF 2" CRUSHED ROCK MULCH, LANDSCAPE FABRIC WITH A MINIMUM WEIGHT OF 4 OZ,/SY, AND WHEREVER NECESSARY, 6" COMMERCIAL GRADE BLACK PLASTIC EDGING TO CONTAIN THE PLANTING BED.
- ALL LANDSCAPE PLANTINGS ARE TO BE WATERED BY THE LANDSCAPE CONTRACTOR THE SAME DAY THAT THE PLANTING OCCURS. IF WATER IS NOT AVAILABLE AT THE BUILDING, THE LANDSCAPE CONTRACTOR SHALL PROVIDE ALTERNATIVE METHODS FOR WATERING.
- SOLITARY TREES DO NOT NEED TO BE EDGED AROUND, HOWEVER ORGANIC WOOD MULCH SHALL BE PLACED AROUND THE TREE IN A MUTTLE RING THAT CONFORMS TO THE DETAIL PROVIDED FOR TREE PLANTINGS.
- CONTRACTOR SHALL PROVIDE WRITTEN WARRANTIES CONFIRMING THE FOLLOWING: FURNISHED TREES GUARANTEED TO LIVE AND REMAIN STRONG, VICOROUS, AND HEALTHY CONDITION FOR 365 DAYS MINIMUM FROM DATE LANDSCAPE INSTALLATION IS ACCEPTED AS COMPLETED.
- LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR WATERING AND CARING FOR ALL PLANT MATERIAL, AND OTHER LANDSCAPING IMPROVEMENTS UNTIL THE DATE OF FINAL INSPECTION AND APPROVAL.


PROPOSED PLANT PALETTE

LOADING DOCK WALL

	SYM.	COMMON NAME	SCIENTIFIC NAME	SIZE	ONTY.
TREES	ш	LITTLE LEAF LINDEN	Quercus marcocarpa	1-1/2" Cal.	4
SHRUBS	AK	ALPINE CURRANT	Ribes alpinum	2 Gallon	80




4 1/2" FULL DEPTH ASPHALT



EXISTING PLANT PALETTE

S AT ASH IKEE	Want	whely
	PLANNER	1-3 19






NTS



SHEET



TREE PLANTING DETAIL

TYPICAL FOR ALL DECIDUOUS, SINGLE-TRUNK, TREES

FOR REGULATORY **REVIEW ONLY-**NOT APPROVED **FOR CONSTRUCTION**

COMPUTER FILE: P:\Bismorck\Centennial Park\Centennial Park\ L8 B 2 Swenson RV.dwg

CHECK BY: JP

DATE: 1/2/19

PROJ.#: 217-11

1

Ш

C3.0